

FILTER HOOD MAINTENANCE MANUAL

DAILY:

Remove and clean filters located over all heavy duty, grease & heat producing cooking equipment. Filters may be manually washed or may be washed in dish machine.

Always replace filters prior to using cooking equipment. Filters must be replaced so that the air inlet slots are vertical.

Wipe clean all visible grease from exposed surfaces.

WEEKLY:

Remove and clean all filters in manner described above.

Empty and clean each grease can located at end of hood.

QUARTERLY:

Inspect duct work and exhaust fan for grease accumulation. Clean if necessary.

PRODUCT WARRANTY

Molitron hoods are warranted to be free from defects in material and workmanship for a period of twelve (12) months from date of initial start-up. Molitron Company, Inc. will replace or repair defective parts at no charge for a period of ninety (90) days from initial start-up. Defective parts must be returned F.O.B. Factory for repair or replacement. All replacement labor charges following initial ninety (90) day warranty shall be paid by customer.

This warranty is conditional upon proper maintenance of all equipment as outlined in the maintenance instructions.

Failure to perform proper maintenance, willfully or otherwise, shall void this warranty in full. Damage resulting from physical abuse such as dropping filters on the floor, or neglect of any kind shall not be covered under this warranty.



1457 Ammons Street, Suite 211 • Lakewood, Colorado 80214

Phone: 303-969-8888 • 800-525-9494 • **Fax:** 303-969-8110

www.molitron.com • cleanair@molitron.com

